

TECHNICAL DATA

CZ 600 LUX

MODEL	LENGTH (mm)	BARREL LENGTH (mm)	WEIGHT (kg)	TWIST RATE / GROOVES	MAGAZINE CAPACITY	SIGHTS
CZ 600 LUX 223 Rem.	997	508	3,1	1:9 / 6	5	Yes
CZ 600 LUX 308 Win.	1040	508	3,7	1:10 / 4	5	Yes
CZ 600 LUX 30-06 Spring.	1053	508	3,7	1:10 / 4	5	Yes
CZ 600 LUX 8 × 57 IS	1053	508	3,7	1:9,5 / 4	5	Yes
CZ 600 LUX 300 Win. Mag.	1155	610	3,9	1:10 / 4	3	Yes

CZ 600 ALPHA

MODEL	LENGTH (mm)	BARREL LENGTH (mm)	WEIGHT (kg)	TWIST RATE / GROOVES	MAGAZINE CAPACITY	SIGHTS
CZ 600 ALPHA 223 Rem.	1096	610	3,0	1:7 / 6	5	No
CZ 600 ALPHA 7,62 × 39	943	457	2,5	1:9,5 / 4	5	No
CZ 600 ALPHA 308 Win.	1020	508	3,2	1:10 / 4	5	No
CZ 600 ALPHA 6,5 Creedmoor	1071	559	3,4	1:7 / 6	5	No
CZ 600 ALPHA 6 mm Creedmoor	1071	559	3,5	1:7 / 6	5	No
CZ 600 ALPHA 6,5 PRC	1122	610	3,6	1:7 / 6	3	No
CZ 600 ALPHA 30-06 Spring.	1033	508	3,3	1:10 / 4	5	No
CZ 600 ALPHA 8 × 57 IS	1033	508	3,3	1:9,5 / 4	5	No
CZ 600 ALPHA 300 Win Mag.	1135	610	3,5	1:10 / 4	3	No

CZ 600 ERGO

MODEL	LENGTH (mm)	BARREL LENGTH (mm)	WEIGHT (kg)	TWIST RATE / GROOVES	MAGAZINE CAPACITY	SIGHTS
CZ 600 ERGO 223 Rem.	1013	508	2,6	1:9 / 6	5	No
CZ 600 ERGO 308 Win.	1038	508	2,9	1:10 / 4	5	No
CZ 600 ERGO 6,5 Creedmoor	1089	559	3,0	1:7 / 4	5	No
CZ 600 ERGO 30-06 Spring.	1052	508	2,9	1:10 / 4	5	No
CZ 600 ERGO 8 × 57 IS	1052	508	2,9	1:9,5 / 4	5	No
CZ 600 ERGO 300 Win. Mag.	1154	610	3,0	1:10 / 4	3	No

CZ 600 RANGE

MODEL	LENGTH (mm)	BARREL LENGTH (mm)	WEIGHT (kg)	TWIST RATE / GROOVES	MAGAZINE CAPACITY	SIGHTS
CZ 600 RANGE 223 Rem.	1113	610	3,8	1:9 / 6	5	No
CZ 600 RANGE 308 Win.	1140	610	4,6	1:10 / 4	5	No
CZ 600 RANGE 6,5 Creedmoor	1140	610	4,6	1:7 / 6	5	No
CZ 600 RANGE 6 mm Creedmoor	1140	610	4,6	1:7 / 6	5	No
CZ 600 RANGE 6,5 PRC	1190	660	4,6	1:7 / 6	3	No
CZ 600 RANGE 300 Win. Mag.	1203	660	4,9	1:10 / 4	3	No

CZ 600 TRAIL

MODEL	LENGTH (mm)	BARREL LENGTH (mm)	WEIGHT (kg)	TWIST RATE / GROOVES	MAGAZINE CAPACITY	SIGHTS
CZ 600 TRAIL 223 Rem.	690-890	412	2,8	1:7 / 6	10	No
CZ 600 TRAIL 7,62 × 39	690-890	412	2,8	1:9,5 / 4	10	No

BARREL AND STOCK COMPATIBILITY

	ALPHA STOCK	LUX STOCK	ERGO STOCK	RANGE STOCK	TRAIL STOCK
AMERICAN (THIN-WALLED) BARREL	●	●	●	●	●
SEMI-HEAVY BARREL	●	○	●	●	●
VARMINT (HEAVY) BARREL	●	○	●	●	○

TRIGGER	STOCK	STOCK FINISH	CHEEKPIECE	L.O.P. (mm)	BARREL	THREAD	RECEIVER SIZE
Single-stage, adjustable	Walnut	Oil	Yes	370	Cold hammer forged	M15×1	I (mini)
Single-stage, adjustable	Walnut	Oil	Yes	370	Cold hammer forged	M15×1	II (medium)
Single-stage, adjustable	Walnut	Oil	Yes	370	Cold hammer forged	M15×1	III (long)
Single-stage, adjustable	Walnut	Oil	Yes	370	Cold hammer forged	M15×1	III (long)
Single-stage, adjustable	Walnut	Oil	Yes	370	Cold hammer forged	M15×1	III (long)

TRIGGER	STOCK	STOCK FINISH	CHEEKPIECE	L.O.P. (mm)	BARREL	THREAD	RECEIVER SIZE
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	I (mini)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	I (mini)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	III (long)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	III (long)
Single-stage, adjustable	Polymer	Soft-touch	No	355	Cold hammer forged	M15×1	III (long)

TRIGGER	STOCK	STOCK FINISH	CHEEKPIECE	L.O.P. (mm)	BARREL	–	RECEIVER SIZE
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	I (mini)
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	III (long)
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	III (long)
Single-stage, adjustable	Polymer	Soft-touch	No	370	Cold hammer forged	–	III (long)

TRIGGER	STOCK	STOCK FINISH	CHEEKPIECE	L.O.P. (mm)	BARREL	–	RECEIVER SIZE
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	I (mini)
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	II (medium)
Single-stage, adjustable	Laminated wood	Varnished	Yes adjustable	370	Cold hammer forged	–	III (long)

TRIGGER	STOCK	–	CHEEKPIECE	L.O.P. (mm)	BARREL	THREAD	RECEIVER SIZE
Double-stage, adjustable	Polymer	–	No	147-347	Cold hammer forged	M15×1	I (Trail mini)
Double-stage, adjustable	Polymer	–	No	147-347	Cold hammer forged	M15×1	I (Trail mini)

Disclaimers:

Due to variations in wood density, which is normally encountered with the use of natural materials, overall rifle weight can fluctuate up to +/- 200 grams.

Caliber changes are limited to those compatible with a given receiver.

To comply with legislation in some countries, barrel lengths are measured from the bottom of the chamber to the tip of the muzzle.